




## EO-FLW60



### 60 watt LED Flood Light

| SPECIFICATIONS                    |  |
|-----------------------------------|--|
| Model Number                      | EO_FLW60   |
| Power Consumption                 | 60 watts   |
| LED Consumption                   | 1pcs x 60 watts  |
| LED Initial Flux                  | >5400 lumens   |
| Average Lumens                    | 4m – 142 lux<br>6m – 84 lux<br>8m – 52 lux<br>10m – 37 lux<br>12m – 37 lux   |
| LED Luminous Efficiency           | 85 -100 lumens / watts   |
| Illuminated Area                  | 4m – 7*6 m<br>6m – 11*9 m<br>8m – 14*12 m<br>10m – 18*15 m<br>12m – 21*18 m  |
| Light Angle                       | 120°   |
| Power Factor                      | 0.98   |
| Power Efficiency                  | >90%   |
| Power Factor                      | >0.98  |
| Working Voltage                   | DC 32-36 voltage   |
| Input Voltage                     | AC85~265 voltage, 277-300 voltage / 50-60Hz, DC24-48 voltage   |
| Lamps Efficiency                  | >85%   |
| Storage Temperature               | -25°C to + 85°C  |
| Light Body & Lampshade Material   | Aluminum House & PC/Glass  |
| Light Body and Lampshade Material | Aluminum Alloy and PC  |
| Working Temperature               | - 40°C to + 55°C   |
| IP Rating                         | IP 65  |
| Colour Temperature                | Warm white 3500 kelvin<br>Cool White 6000 kelvin   |
| Colour Index                      | >Ra80  |
| Certificate                       | CS 9567N<br>IEC 60598.2.1B IEC 61346.2.13:2006<br> N28689 |
| Life Expectancy                   | 50,000 + Hrs   |
| Warranty                          | 3 Years  |

This product is eligible for the NSW Energy Savings Scheme  
For more information visit our website: [www.eolighting.com.au](http://www.eolighting.com.au)